

Luna Cleanflush™

Vitreous China 4.5/3 litre Dual Flush
Close-Coupled Rimless Toilet Suite


Designed with the patented Orbital®
50mm Variable Offset Connector



S trap suite pictured



cleanflush





Luna Cleanflush™



Caroma Coolibah is a range of contemporary essentials designed to suite your lifestyle. Combining an enduring design with rimless pan technology, the **Luna Cleanflush™** is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter™ and Caroma Flow Balancer™, the Cleanflush™ pan is innovative and the next evolution in toilets. The S-Trap suite features the Caroma Orbital® connector, a patented 50mm variable offset connector for increased flexibility on setout. The Luna cistern is an integrated system with a high performance outlet valve, fitted with low profile push buttons and is available in a 1/2" B.S.P. back entry option which completely conceals the inlet stop valve and connections for a seamless look.

Pan: **Luna Cleanflush™** 4.5 litre full flush washdown rimless pan. Caroma Orbital® 50mm variable offset connector supplied (*with S-trap suite only*.)

Traps: S and P trap unvented.

Cisterns: **Luna** cistern – has a free fitting lid and is suitable for domestic and light commercial applications. **Vandal Resistant Conversion Kit** – A simple to install conversion kit is available for the standard mechanism to lock the lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109.

Inlet Valve and Overflow: **Standard Bottom Inlet Cistern** – available as right hand inlet which is interchangeable and incorporates the Apollo inlet valve. Internal overflow only. **Optional Back Entry Cistern** – is fitted with a Unifil inlet valve as standard. Available in internal and septic external overflow versions.

Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.

Fixing: The cistern is fixed directly to the pan with a robust base fixing system without the need for wall fixing.

Seats: The **Xena** soft close quick release thermoset toilet seat is provided as standard with this suite.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

