# Technical Data Sheet




# FH30SS


Wall Mounted Fan Heater


Stainless Steel Finish


#### **Dimensions**


Length Width Height 365mm 196mm 110mm











## **Specifications**

Weight 3.4Kg

Colour Stainless steel
Housing material Stainless steel
coated steel

## **Approval**

ESV130657

#### **Features**

- Easy to install
- Powerful, quiet, tangential fan
- Adjustable thermostat
- 3 year extended warranty

# Technical Data Sheet

#### **Product Use**

The FH30SS is used to quickly heat an area

Typical applications:

Bathrooms

#### **Environmental Conditions**

Operation to IEC 721-3-3
Climatic conditions class 3K5
Temperature 0...+50°C
Humidity <95% r.h.

#### **Standards**

Test standards A/S NZS

60335.2.30:2009

Amdts 1-2010.

ERAC 000114

EMC Compliance This is a Level One

product with an C frame motor that has a very low risk of causing EMC

Interference

### **Minimum Mounting Distances**

When choosing a location for the heater the following minimum mounting distances must be observed:

At least 1800mm from the floor up to the heater At least 200mm from the heater to the ceiling At least 450mm from any adjacent walls

At least 700mm from the heater to any objects

below it

### **Ordering**

When ordering please give name and type,

Reference FH30SS

Barcode 9420004902123

### **Technical Data**

Power Supply 230 VAC
Supply Line Fusing max. 10A
For Solid Wires 2 x 1.5mm<sup>2</sup>

Motor 230-240VAC 50Hz

0.3Amp

Motor Insulation Class B1

Motor Protection ThermallyProtected Total Product Wattage 2200-2400Watts

Installed DB rating at 1.5m 45DB